



WYKAZ ZBROJENIA									
Nr pętko	Szczelino [mm]	Łuszczo [mm]	Długość [mm]	Długość ogólna [m]				Uwagi	
Element:		Podgrzewo		85004	85004	85004	85004		
				Ø12	Ø16	Ø25	Ø32		
1	Ø25	111	5975				832,13		
2	Ø25	118	11665				1378,47		
3	Ø25	111	5980				850,46		
4	Ø12	112	1620	181,44					
5	Ø16	184	1555						
6	Ø16	92	1610		298,12			L. wolne	
7	Ø16	92	1645		148,12				
8	Ø16	92	1645		151,34				
9	Ø16	92	1680		162,72				
10	Ø32	78	5015		465,6				
11	Ø32	78	5015				391,17		
12	Ø16	330	4470				274,17		
13	Ø16	165	4430		164,01				
14	Ø32	78	10045		720,95				
15	Ø32	78	11895				811,59		
16	Ø25	72	11000				928,99		
17	Ø16	22	11000		242		792		
18	Ø16	148	5125		759,5				
19	Ø16	70	2245		191,8				
20	Ø12	26	2545		66,17				
21	Ø12	60	1710	104,4					
22	Ø16	10	1315		131,15				
23	Ø16	14	2630		92,82				
24	Ø16	22	2935		64,57				
Długość razem		[m]	352,01	4956,79	3471,06	2405,52			
Masa razem		[kg/m]	0,888	1,578	3,385	6,313			
Masa ogólna		[kg]	312,6	7883,4	1335,6	15186			
Wskaznik z set.				2 x 35/46 = 73,992 km					
				35/46					

Beton fundamentów: C40/50 V=2x89,1=178,2 m³
Beton słupów i oczepów: C40/50 V=2x112,4=224,8 m³
Stal zbroji: B500St G = 73492 kg

[illegible]